

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

naturaliabau

Trade name: MUFFAWAY COLLANTE-RASANTE  
Revision date: 23/10/2018

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

MUFFAWAY

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Preparation for building: glue / leveling / finishing for calcium silicate panels

### 1.3 Details of the supplier of the safety data sheet

#### Supplier (manufacturer/importer/only representative/downstream user/distributor)

AZICHEM Srl

**Street :** Via G. Gentile16/A

**Postal code/city :** 46044 Goito (MN)

**Telephone :** +390376604185/604365

**Telefax :** +39 0376 604398

**Information contact :** info@azichem.com

### 1.4 Emergency telephone number

Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano) (24h)

Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)

Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo)

Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Careggi - Firenze)

Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma)

Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma) Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Skin Sens. 1 ; H317 - Skin sensitisation : Category 1 ; May cause an allergic skin reaction.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

##### Hazard pictograms



Corrosion (GHS05) · Exclamation mark (GHS07)

##### Signal word

Danger

##### Hazard components for labelling

LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5

CEMENT, PORTLAND, CHEMICALS ; CAS No. : 65997-15-1

##### Hazard statements

H318 Causes serious eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

##### Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

naturaliabau

Trade name: MUFFAWAY COLLANTE-RASANTE  
Revision date: 23/10/2018

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water/....
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## 2.3 Other hazards

None

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

LIME (CHEMICAL), HYDRAULIC ; REACH registration No. : 01-2119475523-36 ; EC No. : 285-561-1; CAS No. : 85117-09-5

Weight fraction :  $\geq 20 - < 25$  %

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 STOT SE 3 ; H335

CEMENT, PORTLAND, CHEMICALS ; EC No. : 266-043-4; CAS No. : 65997-15-1

Weight fraction :  $\geq 15 - < 20$  %

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 STOT SE 3 ; H335

#### Additional information

Full text of H- and EUH-statements: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

When in doubt or if symptoms are observed, get medical advice.

#### Following inhalation

Remove victim out of the danger area. Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

#### In case of skin contact

Wash immediately with: Water Remove contaminated, saturated clothing immediately. In case of skin irritation, consult a physician. In case of skin reactions, consult a physician.

#### After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

Never give anything by mouth to an unconscious person or a person with cramps.

### 4.2 Most important symptoms and effects, both acute and delayed

On contact with moist skin may cause thickening, cracking and cracking of the skin. Prolonged contact in combination with existing abrasions can cause burns. Direct contact with the product may cause corneal injury due to mechanical stress, immediate or delayed irritation or inflammation. The direct contact with large quantities of product dry or with projections of wet product can cause effects ranging from irritation ocular moderate (eg. Conjunctivitis or blepharitis) to chemical burns and blindness. Dust may irritate throat and respiratory system. Coughing, sneezing and panting may occur as a result of exposure above the occupational exposure limits. May cause an allergic skin reaction.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Extinguishing powder alcohol resistant foam Carbon dioxide (CO<sub>2</sub>) Water mist

### 5.2 Special hazards arising from the substance or mixture

None

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

naturaliabau

Trade name: MUFFAWAY COLLANTE-RASANTE  
Revision date: 23/10/2018

## 5.3 Advice for firefighters

Remove persons to safety.

### Special protective equipment for firefighters

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Clear spills immediately. Wear a self-contained breathing apparatus and chemical protective clothing.

#### For non-emergency personnel

Remove persons to safety.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3 Methods and material for containment and cleaning up

#### For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

#### For cleaning up

The contaminated area should be cleaned up immediately with: Water Retain contaminated washing water and dispose it.

### 6.4 Reference to other sections

Reference to other sections Safe handling: see section 7 Personal protection equipment: see section 8

## SECTION 7: Handling and storage



### 7.1 Precautions for safe handling

#### Protective measures

##### Specific requirements or handling rules

Do not breathe dust. Do not breathe gas/fumes/vapour/spray. See section 8.

##### Advices on general occupational hygiene

Normal precautions taken when handling chemicals should be observed.

### 7.2 Conditions for safe storage, including any incompatibilities

Only use containers specifically approved for the substance/product.

#### Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place. Protect against UV-radiation/sunlight Humidity.

#### Hints on joint storage

Storage class : 13

Storage class (TRGS 510) : 13

#### Keep away from

Store at least 3 metres apart from: Chemicals/products that react together readily

#### Further information on storage conditions

Keep container tightly closed and in a well-ventilated place.

### 7.3 Specific end use(s)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

naturaliabau

Trade name: MUFFAWAY COLLANTE-RASANTE  
Revision date: 23/10/2018

## Occupational exposure limit values

LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5

Limit value type (country of origin) : OEL ( EC )

Limit value : 1 mg/m<sup>3</sup>

Remark : SCOEL 2008

Version :

Limit value type (country of origin) : STEL ( EC )

Limit value : 4 mg/m<sup>3</sup> / 15 min

Remark : SCOEL 2008

Version :

## DNEL/DMEL and PNEC values

### DNEL/DMEL

Limit value type : DNEL worker (local) ( CEMENT, PORTLAND, CHEMICALS ; CAS No. : 65997-15-1 )

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : 1 mg/m<sup>3</sup>

## 8.2 Exposure controls

### Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

### Personal protection equipment



When using do not eat, drink, smoke, sniff.

### Eye/face protection

#### Suitable eye protection

Eye glasses with side protection DIN EN 166

### Skin protection

#### Hand protection

Tested protective gloves must be worn DIN EN 374

### Respiratory protection

Quarter-face mask (DIN EN 140) Half-face mask (DIN EN 140) Filtering Half-face mask (DIN EN 149)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Safety relevant basis data

Aspect		powder
Colour		light brown
Odour		none
Melting point/melting range :	( 1013 hPa )	No data available
Vapour density	( (air = 1) )	Data not available
Initial boiling point and boiling range :	( 1013 hPa )	No data available
Decomposition temperature :		No data available
Self flammability		not applicable
Flash point :		Not flammable
Flammability (solid, gas)		Data not available
Lower explosion limit :		No data available
Upper explosion limit :		No data available
Explosive properties		Not applicable
Vapour pressure	( 20 °C )	negligible
Density :	( 20 °C )	No data available
Water solubility :	( 20 °C )	almost insoluble
pH :	>	11

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

naturaliabau

Trade name: MUFFAWAY COLLANTE-RASANTE  
Revision date: 23/10/2018

Log Pow	( 20 °C )	not applicable
Viscosity :	( 20 °C )	No data available
Odour threshold		Data not available
Evaporation rate		Data not available
Maximum VOC content (EC) :		0 Wt %
Oxidizing properties		Not oxidising

## 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Basic reaction when in mixed with water before to became a solid inert compound.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions. See section 7. No additional measures necessary.

### 10.3 Possibility of hazardous reactions

No hazardous reactions when stored and handled properly.

### 10.4 Conditions to avoid

Protect from contact with water to avoid solidification of the product.

### 10.5 Incompatible materials

Acid

### 10.6 Hazardous decomposition products

None

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute effects

##### Acute oral toxicity

Parameter :	LD50 ( LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5 )
Exposure route :	Oral
Species :	Rat
Effective dose :	> 2000 mg/kg bw/day
Method :	OECD 425

It has no significant toxicity properties.

##### Acute dermal toxicity

Parameter :	LD50 ( CEMENT, PORTLAND, CHEMICALS ; CAS No. : 65997-15-1 )
Exposure route :	Dermal
Species :	Rabbit
Effective dose :	> 2000 mg/kg bw/day
Exposure time :	24 days

It has no significant toxicity properties.

#### Irritant and corrosive effects

##### Primary irritation to the skin

On contact with moist skin may cause thickening, cracking and cracking of the skin. Prolonged contact in combination with existing abrasions can cause burns.

##### Irritation to eyes

Direct contact with the product may cause corneal injury due to mechanical stress, immediate or delayed irritation or inflammation. The direct contact with large quantities of product dry or with projections of wet product can cause effects ranging from irritation ocular moderate (eg. Conjunctivitis or blepharitis) to chemical burns and blindness.

##### Irritation to respiratory tract

Dust may irritate throat and respiratory system. Coughing, sneezing and panting may occur as a result of exposure above the occupational exposure limits.

#### Sensitisation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

naturalia bau

Trade name: MUFFAWAY COLLANTE-RASANTE  
Revision date: 23/10/2018

Eczema can be developed as a result of exposure to dust damp, caused both by the high pH which induces irritant contact dermatitis after prolonged contact, either by an immunological reaction to Cr (VI) soluble which causes allergic contact dermatitis.

#### In case of inhalation

not sensitising.

#### Repeated dose toxicity (subacute, subchronic, chronic)

##### Subacute inhalation toxicity

The available evidence indicates clearly that occupational exposure to cement dust content in the product causes deficits in lung function. However, the evidence available at present are insufficient to establish with certainty the dose-response relationship for these effects.

##### Chronic inhalation toxicity

There were no chronic effects or effects at low concentrations.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The ingredients in this mixture do not meet the criteria for classification as CMR according to CLP.

## SECTION 12: Ecological information

Do not allow uncontrolled discharge of product into the environment.

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter :	LC50 ( LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5 )
Species :	Fresh Water fish
Effective dose :	50,6 mg/l
Exposure time :	96 h
Parameter :	LC50 ( LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5 )
Species :	Saltwater Fish
Effective dose :	457 mg/l
Exposure time :	96 h

##### Acute (short-term) daphnia toxicity

Parameter :	EC50 ( LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5 )
Species :	Freshwater invertebrates.
Effective dose :	49,1 mg/l
Exposure time :	48 h
Parameter :	EC50 ( LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5 )
Species :	Saltwater invertebrates
Effective dose :	158 mg/l
Exposure time :	96 h

##### Chronic (long-term) daphnia toxicity

Parameter :	NOEC ( LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5 )
Species :	Saltwater invertebrates
Effective dose :	32 mg/l
Exposure time :	96 h

##### Acute (short-term) algae toxicity

Parameter :	EC50 ( LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5 )
Species :	Freshwater algae
Effective dose :	184,57 mg/l
Exposure time :	72 h
Parameter :	EC0 ( LIME (CHEMICAL), HYDRAULIC ; CAS No. : 85117-09-5 )
Species :	Freshwater algae
Effective dose :	48 mg/l
Exposure time :	72 h

### 12.2 Persistence and degradability

Poorly watersoluble, inorganic product. Can be mechanically precipitated to a large extent in biological sewage plants.

### 12.3 Bioaccumulative potential

not applicable

### 12.4 Mobility in soil

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

naturaliabau

Trade name: MUFFAWAY COLLANTE-RASANTE  
Revision date: 23/10/2018

Low solubility in soil.

## 12.5 Results of PBT and vPvB assessment

This product is none, or does not contain a substance called a PBT or vPvB

## 12.6 Other adverse effects

No information available.

## 12.7 Additional ecotoxicological information

None

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product/Packaging disposal

Dispose according to legislation.

## SECTION 14: Transport information

### 14.1 UN number

No dangerous good in sense of these transport regulations.

### 14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

### 14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

### 14.4 Packing group

No dangerous good in sense of these transport regulations.

### 14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

### 14.6 Special precautions for user

None

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU legislation

Regulation (EC) 1907/2006 (REACH).

Regulation (EC) No 1272/2008 (CLP).

Regulation (EU) 2015/830 requirements for the compilation of safety data sheets.

Amendings, for the purposes of its adaptation to technical and scientific progress, Regulation (EC) No 1272/2008:

Commission Regulation (EC) No 790/2009 (I ATP). Commission Regulation (EU) No 286/2011(II ATP). Commission Regulation

(EU) No 618/2012 (III ATP). Commission Regulation (EU) No 487/2013 (IV ATP). Commission Regulation (EU) No 944/2013

(V ATP). Commission Regulation (EU) No 605/2014 (VI ATP). Commission Regulation (EU) No 1297/2014 (VII ATP).

Commission Regulation (EU) No 2015/1221 (VIII ATP).

#### Other regulations (EU)

**Regulation (CE) 1907/2006: Substance of very high concern included in the SVHC Candidate List**

None

#### National regulations

Italy: Legislative Decree 81/2008 (Consolidated Law on protection of health and safety at work), as amended and Directive 2009/161/UE - chemical risk assessment in accordance with Title IX

#### Water hazard class (WGK)

Class : nwg (Non-hazardous to water) Classification according to VwVwS

### 15.2 Chemical safety assessment

not applicable



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

naturaliabau

Trade name: MUFFAWAY COLLANTE-RASANTE

Revision date: 23/10/2018

## SECTION 16: Other information

### 16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 08. Occupational exposure limit values

### 16.2 Abbreviations and acronyms

#### LEGENDA:

ADR:	Accord européen relative au transport international des marchandises dangereuses par route (accordo europeo relativo al trasporto internazionale delle merci pericolose su strada)
ASTM:	ASTM International, originariamente nota come American Society for Testing and Materials (ASTM)
EINECS:	European Inventory of Existing Commercial Chemical Substances (Registro Europeo delle Sostanze chimiche in Commercio)
EC(0/50/100):	Effective Concentration 0/50/100 (Concentrazione Effettiva Massima per 0/50/100% degli Individui)
LC(0/50/100):	Lethal Concentration 0/50/100 (Concentrazione Letale per 0/50/100% degli Individui)
IC50:	Inhibitor Concentration 50 (Concentrazione Inibente per il 50% degli Individui)
NOEL:	No Observed Effect Level (Dose massima senza effetti)
NOEC:	No Observed Effect Concentration (Concentrazione massima senza effetti)
LOEC:	Lowest Observed Effect Concentration (Concentrazione massima alla quale è possibile evidenziare un effetto)
DNEL:	Derived No Effect Level (Dose derivata di non effetto)
DMEL:	Derived Minimum Effect Level (Dose derivata di minimo effetto)
CLP:	Classification, Labelling and Packaging (Classificazione, Etichettatura e Imballaggio)
CSR:	Rapporto sulla Sicurezza Chimica (Chemical Safety Report)
LD(0/50/100):	Lethal Dose 0/50/100 (Dose Letale per 0/50/100% degli Individui)
IATA:	International Air Transport Association (Associazione Internazionale del Trasporto Aereo)
ICAO:	International Civil Aviation Organization (Organizzazione Internazionale dell'Aviazione Civile)
Codice IMDG:	International Maritime Dangerous Goods code (Codice sul Regolamento del Trasporto Marittimo)
PBT:	Persistent, bioaccumulative and toxic (sostanze persistenti bioaccumulabili e tossiche)
RID:	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regolamento concernente il trasporto Internazionale ferroviario delle merci Pericolose)
STEL:	Short term exposure limit (limite di esposizione a breve termine)
TLV:	Threshold limit value (soglia di valore limite)
TWA:	Time Weighted Average (media ponderata nel tempo)
UE:	Unione Europea
vPvB:	Very persistent very bioaccumulative (sostanze molto persistenti e molto bioaccumulabili)
N.D.:	Non disponibile.
N.A.:	Non applicabile
AwSV.:	Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV))
PNEC:	Predicted No Effect Concentration
PNOS:	Particulates not Otherwise Specified
BOD:	Biochemical Oxygen Demand
COD:	Chemical Oxygen Demand
BCF:	BioConcentration Factor
TRGS :	Technische Regeln für Gefahrstoffe -Technical Rules for Hazardous Substances, defined by The Federal Institute for Occupational Safety and Health, Germany
LCLo:	Lethal Concentration Low (La minima concentrazione letale)
ThOD:	Theoretical Oxygen Demand

### 16.3 Key literature references and sources for data

None

### 16.4 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

calculated.

### 16.5 Relevant H- and EUH-phrases (Number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

naturaliabau

Trade name: MUFFAWAY COLLANTE-RASANTE  
Revision date: 23/10/2018

---

H335 May cause respiratory irritation.

## 16.6 Training advice

None

## 16.7 Additional information

None

---

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

---